

FLUORESCENT BALLAST SPECIFICATIONS

DESCRIPTION

Model No.	Ballast Type	Starting Type	Qty of Lamps	Lamp Type
BL-1520LB-2	ELECTRONIC	INSTANT START	2	F15T8, F17T8, F20T8, F20T9

ELECTRICAL CHARACTERISTICS

Input Voltage	Frequency	Lamp Watts	Input Watts	Input Current	THD	Power Factor	Sound Rated
120	60Hz	2x20W	34.6W	<0.55A	<160%	>0.55	A
Min. Starting Temp	Heat Protection Level	Outdoor Type	Open Circuit Voltage	Ballast Frequency	NO PCBS		
0°F/-18°C	CLASS P	TYPE 1	600V	>40KHZ			

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS					
	Units	M	L	W	H	
	Inch	5.57	6.71	1.75	1.31	
	TOL(+/-)	0.05	0.05	0.05	0.05	
LEAD LENGTH						
Unit	Black	White	Red	Yellow	Green	Blue
Inch	13	13	20	20	7.09	7.09
TOL(+/-)	+0.5, -0	+0.5, -0	+0.5, -0	+0.5, -0	+0.5, -0	+0.5, -0

BALLAST LABEL

	<p>USE FOR 2 LAMPS F15T8(15W), F17T8(17W) F20T8(20W), F20T9(20W) Instant Start Normal Power Factor Class P, Outdoor Type1</p> <p>CAUTION: Disconnect All Input Power Before Installing Or Servicing.</p>	<p style="text-align: center;">Electronic Ballast</p> <p style="text-align: center;">CAT:2040 MODEL:BL-1520LB-2</p>
--	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------

USPAR ENTERPRISES INC.

ADD: 13404 Monte Vista Ave Chino, CA 91710
 WEBSITE: www.uspar.com

TEL: 1-909-591-7506
 FAX 1-909-590-3220