

FLUORESCENT BALLAST SPECIFICATIONS

DESCRIPTION

Model No.	Ballast Type	Starting Type	Qty of Lamps	Lamp Type
BL-1740XLT-MV-1/2	ELECTRONIC	INSTANT START	1 or 2	F32T8, F25T8, F17T8

ELECTRICAL CHARACTERISTICS

Input Voltage	Frequency	Lamp Watts	Input Watts	Input Current	THD	Power Factor	Sound Rated
120v to 277v	60 Hz	32w	32w	120V MAX .52A 277V MAX .23A	<10%	>0.98	A
Min. Starting Temp	Heat Protection Level	Outdoor Type	Open Circuit Voltage	Ballast Frequency	NO PCBs		
0°F/-18°C	CLASS P	TYPE 1	600V	>40kHz			

PHYSICAL CHARACTERISTICS

Ballast dimensions Unit: inch 	CASE DIMENSIONS					
	Units	M	L	W	H	
	Inch	9.5	8.5	1.675	1.25	
TOL(+/-)	0.05	0.05	0.05	0.05		
LEAD LENGTH						
Unit	Black	White	Red	Yellow	Green	Blue
Inch	1x24"	1x24"	1x36"	N/A	N/A	2x34"
TOL(+/-)	+0.5, -0	+0.5, -0	+0.5, -0	+0.5, -0	+0.5, -0	+0.5, -0

Physical Characteristics drawing denoted in mm please divide by 25.4 for inches

BALLAST LABEL

USPAR ENTERPRISES INC.

ADD: 13404 Monte Vista Ave Chino, CA 91710
 WEBSITE: www.uspar.com

TEL: 1-909-591-7506
 FAX: 1-909-590-3220