

FLUORESCENT BALLAST SPECIFICATIONS

DESCRIPTION

Model No.	Ballast Type	Starting Type	Qty of Lamps	Lamp Type
BL-1740XLT-MV-3/4	ELECTRONIC	INSTANT START	3 or 4	F32T8, F25T8, F17T8

ELECTRICAL CHARACTERISTICS

Input Voltage	Frequency	Lamp Watts	Input W+D29atts	Input Current	THD	Power Factor	Sound Rated
120V to 277V	60Hz	32W	128W	120V MAX 1.09A 277V MAX .472A	<10%	>0.98	A
Min. Starting Temp	Heat Protection Level	Outdoor Type	Open Circuit Voltage	Ballast Frequency	NO PCBs		
0°F/-18°C	CLASS P	TYPE 1	600V	>40KHZ			

PHYSICAL CHARACTERISTICS

Ballast dimensions Unit: inch		CASE DIMENSIONS				
		Units	M	L	W	H
		Inch	9.5	8.5	1.75	1.625
		TOL(+/-)	0.05	0.05	0.05	0.05
LEAD LENGTH						
Unit	Black	White	Red	Yellow	Green	Blue
Inch	1x24"	1x24"	1X24"	N/A	N/A	4X24"
TOL(+/-)	+0.5, -0	+0.5, -0	+0.5, -0	+0.5, -0	+0.5, -0	+0.5, -0

Physical Characteristics drawing denoted in mm please divide by 25.4 for inches

BALLAST LABEL

	Cat#BL-1740XLT-MV-3/4 <small>Model#-E-B708-432UH-MD1</small>	Multi Voltage 120V-277V 50/60Hz							
	<table border="0"> <tr> <td>FOR USE WITH:</td> <td>3(LAMP)</td> <td>4(LAMP)</td> <td> <ul style="list-style-type: none"> 120VAC to 277VAC, 60 Hz Power Factor > 0.98 THD < 10% Min. Starting Temp. -18°C(0°F) Class P Type 1 Outdoor Sound Rating: Class A Disconnect Power Before Servicing </td> </tr> <tr> <td>LAMP TYPE:</td> <td>120/277</td> <td>120/277</td> <td> <ul style="list-style-type: none"> Instant Start-For Use With SHUNTED Lampholders Complies with FCC 47 CFR Part 15 Non-consumer Limit No PCB's Inherent Thermal Protection Ballast A Light-conductance Protection Thermistors Integrate </td> </tr> </table>	FOR USE WITH:		3(LAMP)	4(LAMP)	<ul style="list-style-type: none"> 120VAC to 277VAC, 60 Hz Power Factor > 0.98 THD < 10% Min. Starting Temp. -18°C(0°F) Class P Type 1 Outdoor Sound Rating: Class A Disconnect Power Before Servicing 	LAMP TYPE:	120/277	120/277
FOR USE WITH:	3(LAMP)	4(LAMP)	<ul style="list-style-type: none"> 120VAC to 277VAC, 60 Hz Power Factor > 0.98 THD < 10% Min. Starting Temp. -18°C(0°F) Class P Type 1 Outdoor Sound Rating: Class A Disconnect Power Before Servicing 						
LAMP TYPE:	120/277	120/277	<ul style="list-style-type: none"> Instant Start-For Use With SHUNTED Lampholders Complies with FCC 47 CFR Part 15 Non-consumer Limit No PCB's Inherent Thermal Protection Ballast A Light-conductance Protection Thermistors Integrate 						

USPAR ENTERPRISES INC.

ADD: 13404 Monte Vista Ave Chino, CA 91710
 WEBSITE: www.uspar.com

TEL: 1-909-591-7506
 FAX: 1-909-590-3220