

FLUORESCENT BALLAST SPECIFICATIONS

DESCRIPTION

Model No.	Ballast Type	Starting Type	Qty of Lamps	Lamp Type
BL-2022CB	ELECTRONIC	INSTANT START	1	FC6T9, FC8T9

ELECTRICAL CHARACTERISTICS

Input Voltage	Frequency	Lamp Watts	Input Watts	Input Current	THD	Power Factor	Sound Rated
120	60Hz	22W	19.3W	<0.32A	<150%	>0.50	A
Min. Starting Temp	Heat Protection Level	Outdoor Type	Open Circuit Voltage	Ballast Frequency	NO PCBS		
0°F/-18°C	CLASS P	TYPE 1	600V	>40KHZ			

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS					
	Units	M	L	W	H	
	Inch	5.57	6.71	1.75	1.31	
	TOL(+/-)	0.05	0.05	0.05	0.05	
LEAD LENGTH						
Unit	Black	White	Red	Yellow	Green	Blue
Inch	11.03	11.03	/	7.09	7.09	/
TOL(+/-)	+0.5, -0	+0.5, -0	/	+0.5, -0	+0.5, -0	/

BALLAST LABEL

 120V - 60Hz INPUT CURRENT 0.36A LISTED FLUORESCENT BALLAST 22VE E244627 IQ07 www.innovativelighting.cn	USE FOR 1 LAMP FC6T9(20W),FC8T9(22W) Instant Start No PCBs Normal Power Factor Class P, Outdoor Type1 CAUTION: Disconnect All Input Power Before Installing Or Servicing.	Electronic Ballast CAT:1340-S MODEL:BL-2022CB
---	---	---

USPAR ENTERPRISES INC.

ADD: 13404 Monte Vista Ave Chino, CA 91710
 WEBSITE: www.uspar.com

TEL: 1-909-591-7506
 FAX: 1-909-590-3220