

FLUORESCENT BALLAST SPECIFICATIONS


DESCRIPTION

Model No.	Ballast Type	Starting Type	Qty of Lamps	Lamp Type
BL-3040CB	ELECTRONIC	INSTANT START	1	FC10T9, FC12T9, FC16T9



ELECTRICAL CHARACTERISTICS

Input Voltage	Frequency	Lamp Watts	Input Watts	Input Current	THD	Power Factor	Sound Rated
120	60Hz	32W	24.7W	<0.40A	<140%	>0.52	A
Min. Starting Temp	Heat Protection Level	Outdoor Type	Open Circuit Voltage	Ballast Frequency	NO PCBs		
0°F/-18°C	CLASS P	TYPE 1	600V	>40KHZ			

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS						
	Units	M	L	W	H		
	Inch	5.57	6.71	1.75	1.31		
	TOL(+/-)	0.05	0.05	0.05	0.05		
LEAD LENGTH							
Unit	Black	White	Red	Yellow	Green	Blue	
Inch	11.03	11.03	/	7.09	7.09	/	
TOL(+/-)	+0.5, -0	+0.5, -0	/	+0.5, -0	+0.5, -0	/	

BALLAST LABEL

 <p>120V - 60Hz INPUT CURRENT 0.36A</p> <p>LISTED FLUORESCENT BALLAST 22VE</p> <p>E244627 1Q07</p> <p>www.innovativelighting.cn</p>	<p>USE FOR 1 LAMP FC10T9(30W),FC12T9(32W) FC16T9(40W)</p> <p>Instant Start No PCBs Normal Power Factor CLASS P, OUTDOOR TYPE 1</p> <p>CAUTION: Disconnect All Input Power Before Installing Or Servicing.</p>	<p style="text-align: center;">Electronic Ballast</p> <p style="text-align: center;">CAT:1340-S MODEL:BL-3040CB</p> 
--	---	---

USPAR ENTERPRISES INC.

ADD: 13404 Monte Vista Ave Chino, CA 91710
WEBSITE: www.uspar.com

TEL: 1-909-591-7506
FAX 1-909-590-3220