



FLUORESCENT BALLAST SPECIFICATIONS


DESCRIPTION

Model No.	Ballast Type	Starting Type	Qty of Lamps	Lamp Type
BL-3040LB-1	ELECTRONIC	INSTANT START	1	F30T12, F32T8, F34T12, F40T12

ELECTRICAL CHARACTERISTICS

Input Voltage	Frequency	Lamp Watts	Input Watts	Input Current	THD	Power Factor	Sound Rated
120	60Hz	32W	28.8W	<0.46A	<140%	>0.55	A
Min. Starting Temp	Heat Protection Level	Outdoor Type	Open Circuit Voltage	Ballast Frequency	NO PCBS		
0°F/-18°C	CLASS P	TYPE 1	600V	>40KHZ			

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS					
	Units	M	L	W	H	
	Inch	5.57	6.71	1.75	1.31	
	TOL(+/-)	0.05	0.05	0.05	0.05	
LEAD LENGTH						
Unit	Black	White	Red	Yellow	Green	Blue
Inch	13	13	28	/	/	7.09
TOL(+/-)	+0.5, -0	+0.5, -0	+0.5, -0	/	/	+0.5, -0

BALLAST LABEL

 <p>FOSHAN INNOVATIVE LIGHTING CO.,LTD.</p> <p>120V - 60Hz INPUT CURRENT 0.36A</p> <p>LISTED FLUORESCENT BALLAST 22VE</p> <p>E244627 1108</p> <p>www.innovativelighting.cn</p>	<p>USE FOR 1 LAMP F30T12(30W),F32T8(32W) F40T12(40W)</p> <p>Instant Start</p> <p>Normal Power Factor</p> <p>CLASS P, Outdoor Type 1</p> <p>CAUTION: Disconnect All Input Power Before Installing Or Servicing.</p>	<p style="text-align: center;">Electronic Ballast</p> <p style="text-align: center;">CAT:2040 MODEL:BL-3040LB-1</p> 
--	---	---

USPAR ENTERPRISES INC.

ADD: 13404 Monte Vista Ave Chino, CA 91710
WEBSITE: www.uspar.com

TEL: 1-909-591-7506
FAX 1-909-590-3220