

FLUORESCENT BALLAST SPECIFICATIONS

DESCRIPTION

Model No.	Ballast Type	Starting Type	Qty of Lamps	Lamp Type
BL-6075LBX-2	ELECTRONIC	INSTANT START	1 or 2	F96T12/75W, F96T12/60W, F84T12, F72T12, F64T12, F60T12

ELECTRICAL CHARACTERISTICS

Input Voltage	Frequency	Lamp Watts	Input Watts	Input Current	THD	Power Factor	Sound Rated
120V	60Hz	75W, 60W, 70W, 55W,	135W	1.18A	<20%	0.95	A
Min. Starting Temp	Heat Protection Level	Outdoor Type	Open Circuit Voltage	Ballast Frequency	NO PCB'S		
0°F/-18°C	CLASS P	TYPE 1	600V	>40kHz			

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS						
	Units	M	L	W	H		
	Inch	8.9	9.5	2.38	1.57		
	TOL(+/-)	0.05	0.05	0.05	0.05		
LEAD LENGTH							
Unit	Black	White	Red	Yellow	Green	Blue	
Inch	1x44	1x44	1x68	N/A	N/A	2x44	
TOL(+/-)	+0.5, -0	+0.5, -0	+0.5, -0	+0.5, -0	+0.5, -0	+0.5, -0	+0.5, -0

BALLAST LABEL

USPAR ENTERPRISES INC.

ADD: 13404 Monte Vista Ave Chino, CA 91710
 WEBSITE: www.uspar.com

TEL: 1-909-591-7506
 FAX 1-909-590-3220